



CRB Multi 15W-40 CK-4

Diesel Engine Oil

Description

CRB Multi 15W-40 CK-4

Castrol CRB Multi 15W-40 CK-4 is a multipurpose heavy duty diesel engine oil, designed to provide superior protection. Conforming to the strict requirements of PC-11 engine oil technology, it can be used in diesel engines where API CK-4, CJ-4 and below is required. It is engineered to help give long and healthy engine life, giving you peace of mind that your diesel engines are protected in a variety of applications and duty cycles.

Application

MAIN BENEFITS:

Castrol CRB Multi 15W-40 CK-4 is a versatile product which can be used in a wide range of heavy duty and commercial vehicles commercial vehicles which makes it ideal for use in mixed fleets. Its special formulation helps to keep the engine cleaner, giving more reliable engine protection and thus prolonging engine life across different vehicles in the fleet.

Castrol CRB Multi 15W-40 CK-4 provides:

- Protection against oil thickening and deposit build up in critical engine parts
- Protection from wear and deposits
- Better shear stability and protection against viscosity loss for reliable engine protection
- Its versatile use makes it ideal for mixed fleets enabling product rationalisation for workshops and mixed fleets

Approvals

- API CK-4, CJ-4, CI-4 Plus
- CAT ECF-3
- Cummins CES 20086
- DDC DFS 93K222
- Ford WSS-M2C171-F1
- Mack EOS 4.5
- MB Approval 228.31
- Volvo VDS-4.5
- RVI RLD-3

Typical Characteristics

| Name | Method | Units | CRB Multi 15W-40 |
|---------------------------|------------|--------------------|------------------|
| Appearance | Visual | - | Clear & Bright |
| Total Base Number | ASTM D2896 | mg/g KOH | 10 |
| Sulfated Ash Content | ASTM D874 | % wt. | 1.0 |
| Pour Point | ASTM D97 | C | -42 |
| Viscosity, Kinematic 100C | ASTM D445 | mm ² /s | 15.5 |
| Viscosity, Kinematic 40C | ASTM D445 | mm ² /s | 116 |
| Viscosity Index | ASTM D2270 | None | 140 |
| | | | |

CRB Multi 15W-40 CK-4

30 Apr 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com