



Castrol EDGE10W-30 U.S.

Strength for Maximum Performance

Description

Today's engines continually push the boundaries of technology and engineering. They are smaller and ultra-efficient, without sacrificing performance. Advanced engines challenge the oil with increased pressures. These intense pressures cause friction, which can waste up to 10% of an engine's performance.

Castrol EDGE with patented Fluid TITANIUM transforms its physical structure to be stronger under pressure to keep metal apart and reduces friction for maximum engine performance when you need it most.

Castrol EDGE with Fluid TITANIUM: unlock the true performance of your engine.

Application

Castrol EDGE 10W-30 U.S. is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an API SP, ACEA A1/B1 or earlier specification 10W-30 lubricant.

Advantages

Castrol EDGE 10W-30 U.S. with Fluid TITANIUM is the natural choice for drivers who demand maximum engine performance from today's modern vehicles requiring a high level of protection and higher performance oils.

Castrol EDGE 10W-30 U.S.:

- Transforms to be strongest when the pressure is highest, protecting your engine
- Reduces power-robbing friction across engine speeds and conditions
- Independently tested at the highest standards for proven performance
- Recommended by world-leading car manufacturers
- Protects the engine for the entire drain interval even under extreme pressure

Typical Characteristics

Name	Method	Units	Castrol EDGE 10W-30 U.S
Density @ 15C, Relative	ASTM D4052	g/ml	0.85
Viscosity, Kinematic 100C	ASTM D445	mm²/s	10.5
Viscosity, CCS -25C (10W)	ASTM D5293	mPa.s (cP)	4000
Viscosity, Kinematic 40C	ASTM D445	mm²/s	65
Viscosity Index	ASTM D2270	None	152
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	225
Ash, Sulphated	ASTM D874	% wt	0.78

Product Performance Claims

ACEA A1/B1 API SP ILSAC GF-6

Additional Information

Health and Safety

Based on available information, this product is not expected to produce adverse effect on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office or via the Internet at <u>www.castrol.com/</u><u>us</u>. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment; return used oil to collection center.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com

Castrol EDGE10W-30 U.S. 05 May 2020 Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.