

Castrol Transmax CVT

CVT Fluid

Description

Castrol Transmax CVT, formulated with Smooth Drive Technology™ and premium full-synthetic base oil, is designed for most continuously variable transmissions. Its superior technology enables longer transmission life. Castrol Transmax CVT is suitable for use in most passenger cars fitted with push belt transmissions. Ensuring peace of mind across a wide range of vehicles.

Advantages

- Enhanced friction durability for a smoother drive for longer transmission life.
- Enhanced wear protection for longer transmission life.
- Superior high temperature protection to effectively resist oxidation.
- Superior variator torque capacity that can prevent belt or chain slippage.

Typical Characteristics

Name	Method	Units	Transmax CVT
Density @ 15C, Relative	ASTM D4052	g/ml	0.850
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	35
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.25
Viscosity Index	ASTM D2270	None	178
Pour Point	ASTM D97	°C	-51
Viscosity, Brookfield @ -40C	ASTM D2983	mPa.s (cP)	11100
Flash Point, COC	ASTM D92	°C	218

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Product Performance Claims

Suitable for use where:

Toyota CVT Fluid TC
Toyota CVT Fluid FE
Nissan CVT Fluid NS-1
Nissan CVT Fluid NS-2
Nissan CVT Fluid NS-3
MMC DIAQUEEN ATF SP-III
MMC DIAQUEEN CVT Fluid J1
MMC DIAQUEEN CVT Fluid J4
Mazda CVTF 3320
Subaru i-CVT Fluid
Subaru i-CVT FG
Subaru Lineartronic High Torque Chain CVTF
Daihatsu AMMIX CVT Fluid DC
Daihatsu AMMIX CVT Fluid DFE
Suzuki CVT Fluid 3320
Suzuki CVT Fluid Green 1
Suzuki CVT Fluid Green 2
Suzuki CVTF TC
Suzuki NS-2
Honda HCF-2
Hyundai/Kia SP-III
Chrysler NS-2
Chrysler CVTF+4
Mini Cooper EZL799
Ford CVT23
MB 236.20

User Advice

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through your sales contact office, or via the internet at www.castrol.com. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Transmax CVT

22 Jul 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This Data Sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a valid license. It is the User's obligation to evaluate and use products safely and within the scope advised in the Data Sheet, to assess suitability for the intended application, and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the products. The Seller shall not be responsible for any loss, damage or injury resulting from any abnormal use of the product, from any failure to adhere to recommendations, nor from any hazards or risks which are i) identified in the Data Sheet, ii) inherent in the nature of petroleum products or iii) associated with the petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned). All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road , Wayne, NJ 07470

www.castrol.com