



MMA 160

Rated Input Voltage(V)	Frequency	No-Load voltage	Duty Cycle	Dimension LxWxH	Net Weight
110/220V±15%	50/60HZ	70 ±5V	160A@60% ^o 30°C	33X13X20.5 CM	3.8 KG(APPROX)

MMA:

Rated Input Power	Rated Input Current	Rated Output Current	Rated Output Voltage
5.1KW(110V)/7.2KW(220V)	46.3A(110V)/32.9A(220V)	120A(110V)/160A(220V)	24.8V(110V)/26.4V(220V)

LIFT TIG:

3.0KW(110V)/4.5KW(220V)	27.6A(110V)/20.4A(220V)	120A(110V)/160A(220V)	14.8V(110V)/16.4V(220V)
-------------------------	-------------------------	-----------------------	-------------------------

MMA Max Welding Thickness: 6mm LIFT TIG Max Welding Thickness: 4mm

MMA: E6013/7018 Electrode dia. applicable: Ø1.6-4.0mm

LIFT TIG: TIG Tungsten electrode Max Ø2.4mm

Accessories

1. Power cable 1.8m
2. 300A electroder holder 2.0m cable
3. 300A earth clamp 2.0m cable
4. 110V-220V adapter
5. Steel brush
6. Welding mask
7. Shoulder strap
8. User manual