



## MMA 200

| Rated Input Voltage(V) | Frequency | No-Load voltage | Duty Cycle                | Dimension LxWxH | Net Weight     |
|------------------------|-----------|-----------------|---------------------------|-----------------|----------------|
| 110/220V±15%           | 50/60HZ   | 70 ±5V          | 200A@60% <sup>30</sup> °C | 35X15X23.5 CM   | 4.9 KG(APPROX) |

### MMA:

| Rated Input Power       | Rated Input Current    | Rated Output Current  | Rated Output Voltage    |
|-------------------------|------------------------|-----------------------|-------------------------|
| 5.6KW(110V)/9.6KW(220V) | 51.0A(110V)43.6A(220V) | 130A(110V)/200A(220V) | 25.2V(110V)/28.0V(220V) |

### LIFT TIG:

|                         |                         |                       |                         |
|-------------------------|-------------------------|-----------------------|-------------------------|
| 3.4KW(110V)/6.2KW(220V) | 30.8A(110V)/28.0A(220V) | 130A(110V)/200A(220V) | 15.2V(110V)/18.0V(220V) |
|-------------------------|-------------------------|-----------------------|-------------------------|

Max Welding Thickness: 10mm LIFT TIG Max Welding Thickness: 5mm

**MMA:** E6013/7018 Electrode dia. applicable: Ø1.6-5.0mm

**LIFT TIG:** Tungsten electrode  
Max Ø2.4mm

### Accessories

1. Power cable 1.8m
2. 300A electrode holder 2.5m cable
3. 300A earth clamp 2.0m cable
4. 110V-220V adapter
5. Steel brush
6. Welding mask
7. Shoulder strap
8. User manual